



Massenträgheitsmomente der Tandler PE2 Getriebe-Baureihe

Massenträgheitsmoment I (kg m²)

Getriebetyp	I ₁₂	I ₂₁	I ₃₁		I ₃₂	
			Schnecke 1gängig - 2gängig		Schnecke 1gängig - 2gängig	
PE2-00	0,81566*10 ⁻⁴	7,34094x 10 ⁻⁴	0,11307x 10 ⁻⁴	0,12567x 10 ⁻⁴	0,11315x 10 ⁻⁴	0,12684x 10 ⁻⁴
PE2-01	2,31756x 10 ⁻⁴	13,76335x 10 ⁻⁴	0,25164x 10 ⁻⁴	0,25996x 10 ⁻⁴	0,25162x 10 ⁻⁴	0,26162x 10 ⁻⁴
PE2-A1	6,71473x 10 ⁻⁴	60,43257x 10 ⁻⁴	0,49660x 10 ⁻⁴	0,51744x 10 ⁻⁴	0,49695x 10 ⁻⁴	0,52006x 10 ⁻⁴
PE2-B1	15,02522x 10 ⁻⁴	135,22698x 10 ⁻⁴	0,43310x 10 ⁻⁴	0,45676x 10 ⁻⁴	0,43783x 10 ⁻⁴	0,47557x 10 ⁻⁴
PE2-C1	33,55180x 10 ⁻⁴	301,96650x 10 ⁻⁴	1,21807x 10 ⁻⁴	1,32796x 10 ⁻⁴	1,21661x 10 ⁻⁴	1,32211x 10 ⁻⁴
PE2-D1	70,67815x 10 ⁻⁴	636,10331x 10 ⁻⁴	3,16149x 10 ⁻⁴	3,41869x 10 ⁻⁴	3,15549x 10 ⁻⁴	3,41269x 10 ⁻⁴
PE2-E1	182,22787x 10 ⁻⁴	1640,05046x 10 ⁻⁴	6,68178x 10 ⁻⁴	7,60309x 10 ⁻⁴	6,67320x 10 ⁻⁴	7,59589x 10 ⁻⁴